



For Unmatched Performance **SAY MAGIC**

Magic™, available only from U S Technology Corp., is designed to make man hours in your depainting operation disappear into thin air.

- Performs three to four times faster than traditional plastic blasting media.
- Based on emerging nanocomposite technology.
- Engineered specifically for high-performance aerospace blasting environment, where rapid depainting is a priority.
- Tremendous savings in material and labor cost.

Product Trade Name:	Magic
Product Description:	A Nanostructured composite abrasive media made of blended amino thermoset resins and reinforcing fiber.
Product Part Number:	USTMA013060 - 250 lb. net wt. Drum USTMA023060 - 1750 lb. net wt. Supersack
Size:	30/60 Mesh - U.S. Standard sieve*
Hardness:	60 Barcol
Density:	1.40 to 1.46
Strip Rate:	@ 30 PSI 4 sq. ft/min. @ 25 PSI 3 sq. ft/min. 1/2" Double venturi nozzle Mil Spec epoxy primer, urethane topcoat
Consumption:	@ 30 PSI 6% @ 25 PSI 5% * Mil Spec test method
Conductivity*:	100.00 u ^s max.
Heavy Particles*:	0.02 max.
Light Particles*:	1.00 max.
AntiStatic Level*:	7/8 of an inch.
Specific Gravity:	1.46 max.
ASH:	2.00% max.
Extract:	1.00% max.
pH:	8 max.

*Mil Spec Mil P85891 test protocol

MAGiC

US TECHNOLOGY CORPORATION

1446 W. Tuscarawas St.
Canton, OH 44702

Phone: 330-455-1181

Toll Free: 800-634-9185

Fax: 330-455-1191

www.ustechnology.com

info@ustechnology.com