



Silica-Free Mineral Abrasive

SteelMagic® is designed for removal of thick coatings on heavier steel substrates like bridges, tanks, ships, refineries, pipelines and heavy equipment.

Steel-Magic will remove heavier enhanced coatings like epoxy and polyurethane at twice the strip rate with less dust than media previously available and the surface profile can be controlled by adjusting the pressure.

Depending on the application, Steel-Magic can be blasted at a lower pressure (35-80psi) and be recycled up to 5 times, or it can be blasted at a higher pressure (100-120 psi) and used as a single shot media.

Product Trade Name: SteelMagic®

Product Description: Silica-Free Dense Particle Mineral Abrasive

Product Part Number: USTSM011040 - 2000lb. supersack (coarse)
 USTSM021040 - 300lb. drums (coarse)
 USTSM031040 - 50lb. boxes (coarse)
 USTSM012060 - 2000lb. supersack (med.)
 USTSM022060 - 300lb. drums (med.)
 USTSM032060 - 50lb. boxes (med.)

Size: Coarse 10/40 Mesh - U.S. Standard Sieve
 Med. 20/60 Mesh - U.S. Standard Sieve

Hardness: 7.0 Mohs

Bulk Density: 118.5 lbs./ft³

STEELMAGIC®
US TECHNOLOGY CORPORATION

1446 W. Tuscarawas St.

Canton, OH 44702

Phone: 330-455-1181

Toll Free: 800-634-9185

Fax: 330-455-1191

www.ustechnology.com

info@ustechnology.com